

# Maximum Thickness binding table

Same diameters of wire, close different maximum thicknesses of paper on different machines.

Attention: values may change depending on the kind of paper used. Ask for details.

Diameter		Business Line	MP300 FP340 MP600	P500 P800	TP480MKII WB360 TP340	R500TS R522 R800	R422	B535TS B599HF DP4500	PB796HF PB799	PB735HDDP
Inches	mm.									
3/16"	4,7	4	4	4		3,5			3,5	3,5
1/4"	6,3	5,5	5,5	5,5	5,5	4,8	3*	5	4,8	4,8
5/16"	7,9	7	7	7	7	6,3	7	6,5	6,3	6,3
3/8"	9,5	8,5	8,5	8,5	8,5	8	8,5	8,5		8
7/16"	11	10	10	10	10	9,5	10	10		9,5
1/2"	12,7	11,5	11,5	11,5	11,5	10,5	11,5	11,5		10,5
9/16"	14,3	13	13	13	13	11,5	13	12,5		11
5/8"	16	15	15	15	15	13***	15	14		
3/4"	19	18	18	18	18	15***	18	17		
7/8"	22	20	20	20	20		20	20		
1"	25,4	24	24	24	24		24	23		
1 - 1/8"	28,5		26,5	26,5				26,5		
1 - 1/4"	31,7		29	29				28**		

\* This is a minimum thickness

\*\* Only B-535 T.S.

\*\*\* Only R522